

			ISEKI			
			NEW			
			SA600-FSE4		SA600-FE4	
Dimension	Length	(mm)	1,750		←	
	Width	(mm)	700		←	
	Height	(mm)	1,100		←	
	Weight	(kg)	72		←	
Engine	Model name		Kawasaki FJ180		←	
	Type		OHV		←	
	Displacement	(L)	0.179		←	
	Max output	KW/min <sup>-1</sup>	4.3/ 2,000		←	
		PS/min <sup>-1</sup>	5.9 / 2,000		←	
	Air cleaner		Dry		←	
	Fuel		Gasoline		←	
	Fuel tank capacity	(L)	3.6		←	
	Type		Recoil starter		←	
Emission regulation		CE marking		←		
Main clutch system			Deadman(Belt tension)		←	
Transmission type			Belt⇒Gear⇒Chain		←	
Tire (option)			6.00-12 (Φ636mm)		←	
Number of speed			F6/R2		←	
Shift type			Gear(F3-R1)xGear(2)		Gear(F3-R1)xBelt(2)	
Sub shift			Gear(2)		Belt(2)	
			rated speed	Max speed	rated speed	
Speed (km/h) (at rated engine speed) Tire size:6.00-12	Forward 1(F1xL)		1.2	1.3	←	
	Forward 2(F2xL)		3.0	3.2	←	
	Forward 3(F3xL)		5.2	5.6	←	
	Reverse1(R1xL)		1.9	2	←	
	Forward 1(F1xH)		1.7	1.8	←	
	Forward 2(F2xH)		4.2	4.5	←	
	Forward 3(F3xH)		7.4	7.9	←	
Reverse1(R1xH)		2.7	2.8	←		
Rotation speed(min-1) (at rated engine speed)	Forward 1(F1xL)		10.0	10.7	←	
	Forward 2(F2xL)		25.2	26.9	←	
	Forward 3(F3xL)		43.7	46.6	←	
	Reverse1(R1xL)		15.8	16.9	←	
	Forward 1(F1xH)		14.0	14.9	←	
	Forward 2(F2xH)		35.4	37.8	←	
	Forward 3(F3xH)		61.5	65.6	←	
Reverse1(R1xH)		22.3	23.8	←		

SA250SE4			
Dimension	Overall length	(mm)	1,550
	Overall width	(mm)	860
	Overall height	(mm)	1,060
	Weight	(kg)	65
Engine	Model		SUBARU EX17D
	Type		OHC
	Total Displacement	(L)	0.169
	Output/engine speed	KW/(rpm)	4.2/4,000
		PS(rpm)	5.7/4,000
	Air cleaner		Dry
	Fuel		Gasoline
	Fuel tank capacity	(L)	3.6
	Starting method		Recoil starter
European emission regulation		Euro STAGE2	
Main clutch		Deadman(Belt tension)	
Transmission Type		V-belt⇒Gear⇒Chain	
No. of speeds		F:4, R:2	
Shift Type		Gear(F2-R1)x Gear(2)	
Rotation Speed(min-1) at rated engine speed	Forward 1	Low	25.7
	Forward 2		66.5
	Reverse 1		16.4
	Forward 3	High	38.6
	Forward 4		99.7
	Reverse 2		24.6
Rotor	Diameter of rotor	(mm)	320
	No. of rotor		6
	Tilling width	(mm)	855,560
Handle	Handle shape		Y-shape
	Vertical height adjustment		Infinity
	Horizontal adjustment		3 positions
Width of fender		600	
Rear hitch		Standard	
PTO		No	
Transportation wheel		1 wheel (Front)	
Option parts	Tire(5.00-10)		Local arrangement
	Wheel tube		Local arrangement
	Front weight		Local arrangement
	Front hitch		Local arrangement